

Silent & Low Speed Granulator AH

Blades of AH-series proceeds primary granulating and fine granulating at the same time. The advanced double-edge design on cutter minimizes the resistance of material and improves the cutting. After primary crushing, the material requires only low speed(25-30rpm), low motor power(1-5HP) to have the result of low noise, little dust, and even granulated material. (There are 4x4.5mm and 6x7mm optional tooth roller cutter) Especially suitable to apply AH series that the work requirements are to operate the machine at night time or low-noise environment.



Customised Model: Automatic Material Loading in Bag



AH-160
AH-260
AH-360A
AH-360B



AH-460



AH-560

MODEL	AH-160	AH-260	AH-360A	AH-360B	AH-460	AH-560
Tooth Cut Size(mm)	4*4.5	4*4.5/6*7	4*4.5/6*7	6*7	6*6.7	6*7
Inlet Size(mm)	164*260	256*260	348*260	350*320	440*320	680*440
R.P.M.(rpm)	30	30	30	30	30	30
Power(HP)	2	2	3	3	5	5*2
Machine Weight(kg)	170	210	250	320	415	650
Machine Size(mm)	650*760*940	760*760*1000	830*560*1300	760*920*1600	880*860*1180	1470*1000*1800
Work Capacity(kg/hr)	20~80	30~100	40~120	50~130	80~150	100~200